

RÇN 1500/1800/2000

Nogueira Slasher – Ruggedness and Precision on any terrain.

Designed to cut pastures, tough shrubs, and grasses, the Nogueira Slasher combines ruggedness, precision, and durability, ensuring reliable performance and efficient cutting in any application. Ideal for pastures, road margins, lawns, orchards, and coffee fields, it offers versatility and safety on the job.

Its carbon-steel chassis with reinforced beams and articulated hitch tower allow the brush cutter to follow ground undulations, operating centrally or offset up to 227 mm to the right.

The oil-bathed transmission gearbox, driven by a PTO shaft with a safety overload clutch, ensures long service life and dependability.

HIGHLIGHTS:

- Three-point hitch and coupling;
- High-strength steel blades, reversible for maximum utilization;
- Right-side lateral operation with movable hitch, providing greater flexibility.



Side skids with 5 cutting height adjustment options and replaceable wear shoes.



Front and rear protective deflectors against thrown objects.



Swiveling bearing-mounted gauge wheel.

TECHNICAL FEATURES

Characteristics		SLASHER MODELS		
		RÇN 1500	RÇN 1800	RÇN 2000
Working width	mm	1500	1800	2000
Cutting width	mm	1430	1730	1930
Number of blades	units	2	2	2
Reversible blades		yes	yes	yes
Blade speed	rpm	1036	1036	1036
Cutting height adjustments		5	5	5
Cutting height	mm	35 -175	35 -175	35 -175
Required power at PTO	hp	50	60	70
Required revolution at PTO	rpm	540	540	540
Replaceable skid shoes		yes	yes	yes
Bearing-mounted steel wheel		yes	yes	yes
Safety Guard		yes	yes	yes
Protection		chain	chain	chain
Hitch category		CAT. II	CAT. II	CAT. II
Gearbox oil	L	1,5 (SAE 90 API GL-5)	1,5 (SAE 90 API GL-5)	1,5 (SAE 90 API GL-5)
Length (L)	mm	2277	2547	2277
Height (H)	mm	1124-1264	1124-1264	1124-1264
Width (W)	mm	1600	1900	2100
Transport width (W)	mm	1653	1953	2153
Approximate weight	kg	343	422	470