

SOFTDUO 1300 Fixed Rate

Fertilizers and Distributors

SOFTDUO 1300 is your guarantee of precision and performance! The new **Soft Duo 1300 Fixed Rate** now features:

Hydraulic openings system regulated by a solenoid valve control, allowing for a more uniform and precise distribution, regardless of the rotation and speed of the tractor's movement, correcting application flaws by transitioning to a simple, efficient, and highly accurate application.


Equipped with a robust chassis and the well-known structure of Soft Duo. The distribution disks are made of stainless steel, providing superior durability against any applied product, such as corrosive substances, for example.

It has a set of linear actuators (hydraulic pistons) that allow independent opening and closing of the dosing outlets, regardless of the tractor's speed, maintaining a fixed application rate. It also has eccentric agitators, which do not harm the products and ensure excellent application.

It features a digital controller that handles distribution control via GPS, ensuring that the application is carried out exactly as programmed from the beginning to the end of the job.



Eccentric agitator



Fertilizer flows towards the vanes as a result of rotation




An automatic gearbox transmission system with conjugated gears




Easy-to-change vanes

CALIBRATION KIT INCLUDED


CALIBRATION BOX



GRADUATION BOX



BOX SET



DISTRIBUTION KIT



Características Técnicas

SOFT DUO 1300 FIXED RATE

Working width	From 9 to 24 m
Required revolution at PTO	540 rpm
Required power at PTO	From 30 to 50 hp
Loading capacity	1.300 lt
Weight	302 kg
Side length	2,2 m
Frontal length	1,4 m
Height	1,52 m